



NOTES:

- 1** HORIZONTAL ADJUSTMENT:
 - 1.1. DISTANCE MUST BE 38.0 MAX WHEN FULLY ADJUSTED LEFT.
 - 1.2. DISTANCE MUST BE 41.8 MIN WHEN FULLY ADJUSTED RIGHT.
- 2** LATCH:
 - 2.1. FREE DISTANCE MUST BE MEASURED AS SHOWN.
 - 2.2. LATCH MUST MOVE 4.0 MIN, WHEN LEVER IS ACTUATED.
- 3** DEPTH ADJUSTMENT:
 - 3.1. DISTANCE MUST BE 13.0 ± 0.1 WHEN FULLY ADJUSTED IN.
 - 3.2. DISTANCE MUST BE 15.4 MIN WHEN FULLY ADJUSTED OUT.

	ITEM#: US-CLIP-6W		MATERIAL: ---
	FINISH: ---		WEIGHT: 9
	PROPRIETARY / CONFIDENTIAL		PROJECTION
	THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF HARDWARE RESOURCES INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF HARDWARE RESOURCES INC. IS PROHIBITED.		
TOLERANCE UNLESS OTHERWISE SPECIFIED:	UNITS: mm	DRAWN BY: DENNIS MCGREGOR	DATE: 21MAR14
0 < x < 6.29 ± 0.05 6.30 < x < 12.69 ± 0.10 12.70 < x < 25.39 ± 0.15 25.40 < x ± 0.25 ANGULAR: ±0.5°	SIZE: A4	APPROVED BY:	DATE:
DO NOT SCALE DRAWING	SHEET: 1 OF 1	RELEASE LEVEL: In Work	REVISION: 1.3